

Technical Specifications

Wireless WC-3000 Only

- IEEE 802.11b
- Dual 4 dBi omni directional antennas
- 200mW output at SMA connector
- Range: Up to 1000 feet (300 meters) indoor

Networking 3000/3500

- Auto-IP supports any network configuration
- PPPoE
- IP Multicast
- SMTP Redirection
- Multiple VPN Connection Support
- Dynamic DNS
- DHCP Server, Client, and Relay
- NAT (RFC 1631)
- Transparent HTTP Proxy Server

3500 Only

- Bandwidth limiting globally or per user.

Hardware 3000 Only

- 50 Concurrent Users
- 4 Mbps throughput
- 512 user local database

3500 Only

- 200 Concurrent Users
- 65 Mbps throughput
- 2000 user local database

Security 3000/3500

- Secure HTML Login Page (SSL)
- Extensive System Log (Syslog) Monitoring
- IP and MAC address pass-through and blacklist
- VPN pass-through (IPSec/PPTP/L2TP)
- Web-based management
- Local or remote firmware upgrade
- Hours of service control for public venues
- LAN Device Monitoring and Management
- XML/SOAP secure management
- Customizable Firewall
- Real-time session list
- Remote management IP control
- GRE tunneling

3500 Only

- Port Isolation of "public" and "private" LAN ports
- Customizable Packet Filter

Local Services and Branding 3000/3500

- Walled garden
- Standard or Customized Login, Welcome, Goodbye, Terms of Service, and Logout Pages
- One Time or Time-based Advertisement URLs

3500 Only

- Host complete custom portal and files internally

User Authentication and Accounting 3000/3500

- 'Captive Portal' Login Page Redirection
- Backup, Restore, and Export Local User Database
- Local User Database for Name/Password Logins
- Advanced Local Account Management
- ICOA TollBooth™ Authentication
- Logout Window Timer Control
- Café Account - Time-limited free access
- RADIUS client
- HiltonFamily™ HSIA Authentication
- Simple "Terms of Service" Login Option

Hardware 3000/3500

- 4 Switched 10/100M Fast Ethernet LAN ports
- 8 x 4 x 1 In. / 2.4 Lbs.
- 1 10/100M WAN port
- 0-55° C operating temperature

3500 Only

- 19" 1U rack mount